

# VERTICAL LAMINAR AIR FLOW LAF32-0630



# VERTICAL LAMINAR AIR FLOW LAF32-0630

Engineered to create a particle-free working environment and provide product protection. It is suited for use with non-hazardous contaminants and creates a clean work environment over a wide range of applications.

Used in Electronic sectors, Industrial sectors, Medical, Pharmaceutical, Healthcare.

Also known as Tissue Culture Hood, Laminar Air Flow Cabinet, Laboratory Laminar Flow, Laboratory Laminar Air Flow, Laminar Flow Cabinet, Minimal-Turbulence Air Flow, Laminar Flow Cabinet, Laminar Flow Hood, Laminar Flow.

## LAF32-0630 VERTICAL LAMINAR AIR FLOW

Microprocessor controller

Pre-filter: Polyester fiber, washable

UV Lamp: Emission of 253.7 nanometers



### SPECIFICATIONS

Model	LAF32-0630
Type	Vertical Laminar Flow
Air Flow Velocity	Average of 0.3~0.5m/s, air speed adjustable.
HEPA Filter	99.995% efficiency at 0.3μm
Pre-filter	Polyester fiber, washable
Work Surface Height	/
Max Opening	/
Front Window	/
UV Lamp	15Wx1 Emission of 253.7 nanometers
illuminating Lamp	Fluorescent lamp 8W*1
Display	LED Display
Main Body Material	Cold-rolled steel with anti-bacteria powder coating
Work Table Material	304 stainless steel
Caster	/
Standard Accessory	Fluorescent lamp; UV lamp x2; Water & gas tap.
Optional Accessory	/
Noise	<65dB
Internal Size	630Wx375Dx615H mm
External Size	680Wx410Dx1160 mm
Package Size	840Wx560Dx1380H mm
Gross Weight	50kg
Consumption	160W
Power Supply	AC220V±10%, 50/60 Hz; 110V±10%, 60Hz



**Labstac LLC**

82 Wendell Avenue, STE 100, Pittsfield, MA, 01201, USA  
Email: [contact@m.labstac.com](mailto:contact@m.labstac.com) | Website: [labstac.com](http://labstac.com)