LABSTAC

VERTICAL LAMINAR AIR FLOW LAF36-22L

labstac.com

VERTICAL LAMINAR AIR FLOW LAF36-22L

Engineered to create a particle-free working environment and provide product protection. It is suited for use with non-hazardous contaminants and creates a clean work environment over a wide range of applications.
Used in Pharmaceutical, Pathology lab, Life science research, Plant tissue and cell culture.
Also known as Laminar Air Flow Cabinet, Laboratory Laminar Flow, Laboratory Laminar Air Flow, Laminar Flow Cabinet.

LAF36-22L VERTICAL LAMINAR AIR FLOW

ETL certified, Satisfy North American market.
With memory function in case of power-failure.
Audio and visual alarm(Abnormal airflow velocity).
Interlock function: UV Lamp and blower LED Lamp.

SPECIFICATIONS

Model	LAF36-22L
Type	The ETL certified vertical laminar flow
Airflow Velocity	Average of 80~99 fpm
HEPA Filter	One,99.995% efficiency at 0.3μm
Pre-Filter	Polyester fiber
Work Surface Height	750~1010mm
Max Opening	480mm
Working area Material	304 stainless steel
Main Body Material	1.2mm Cold-rolled steel with anti-bacteria powder coating.
Front Window Material	Motorized, 5mm toughened glass, anti-UV
Waterproof Sockets	One socket (Double type), America standard, Max.Power: 500W
UV Lamp	40W x1
LED Lamp	22W x1
Display	LCD Display
Illumination	≥300lx
Noise	≤68dB(A)
Standard Accessory	Manually height adjustable base stand; LED lamp; UV lamp; Wind speed sensor; Waterproof socket.
Internal Size	1700Wx575Dx625H mm
External Size	1800x700x(2090~2340)mm
Package Size	1940Wx970Dx1560H mm
Gross Weight	320kg
Consumption	1150W
Power Supply	110V±10%V, 60HZ

Labstac LLC
82 Wendell Avenue, STE 100, Pittsfield, MA, 01201, USA
Email: contact@labstac.com | Website: labstac.com