

COMPOUNDING HOOD LAF38-590MA



COMPOUNDING HOOD LAF38-590MA

It has compact desktop design required for operations in an ultra clean, dust free environment. Used for a wide range of applications according to users need.

Used in Research, Pharmaceutical, Medical, Manufacturing areas, Electronic setors, Industrial sectors, Laboratory, Healthcare.

Also known as Desktop Laminar Air flow, Benchtop Laminar Air Flow, Laminar Flow Cabinet, Clean Bench, Laboratory Laminar Flow, Laboratory Laminar Air Flow, Tissue Culture Hood, Laminar Air Flow Cabinet, Minimal-Turbulence Air Flow, Laminar Flow Cabinet, Laminar Flow Hood, Laminar Flow.

LAF38-590MA COMPOUNDING HOOD



SPECIFICATIONS

Model	LAF38-590MA
Туре	Desktop Laminar Flow
Airflow Velocity	0.3~0.8m/s
Filter	Active Carbon Filter
Pre-Filter	/
Max Opening	590mm
Main Body Material	Cold-rolled steel with anti-bacteria power coating
Work Table Material	304 stainless steel
Front Window	Manual, acrylic material
UV Lamp	8W x1 Emission of 253.7 nanometers
LED Lamp	4W x1
Display	LCD Display
Noise	≤60dB
Standard Accessory	Active carbon filter, LED lamp, UV lamp x2, Waterproof socket.
Optional Accessory	Base stand
Internal Size	580Wx520Dx610H mm
External Size	600Wx580Dx1060H mm
Package Size	760Wx740Dx1280H mm
Gross Weight	90kg
Consumption	150W
Power Supply	AC220V±10%, 50/60Hz; 110V±10%, 60Hz

2



Labstac LLC

82 Wendell Avenue, STE 100, Pittsfield, MA, 01201, USA Email: contact@labstac.com | Website: labstac.com