

LABSTAC

COMPOUNDING HOOD LAF38-660M



labstac.com

COMPOUNDING HOOD LAF38-660M

It has compact desktop design required for operations in an ultra clean, dust free environment. Used for a wide range of applications according to users need.

Used in Research, Pharmaceutical, Medical, Manufacturing areas, Electronic setors, Industrial sectors, Laboratory, Healthcare.

Also known as Desktop Laminar Air flow, Benchtop Laminar Air Flow, Laminar Flow Cabinet, Clean Bench, Laboratory Laminar Flow, Laboratory Laminar Air Flow, Tissue Culture Hood, Laminar Air Flow Cabinet, Minimal-Turbulence Air Flow, Laminar Flow Cabinet, Laminar Flow Hood, Laminar Flow.

LAF38-660M COMPOUNDING HOOD



SPECIFICATIONS

Model	LAF38-660M
Type	Desktop Laminar Flow
Airflow Velocity	0.3~0.5m/s
Filter	HEPA Filter
Pre-Filter	Polyester fiber, washable
Max Opening	660mm
Main Body Material	Cold-rolled steel with anti-bacteria power coating
Work Table Material	304 stainless steel
Front Window	Manual, acrylic material
UV Lamp	15W x1 Emission of 253.7 nanometers
LED Lamp	4W x2
Display	LED Display
Noise	≤60dB
Standard Accessory	HEPA filter, LED lamp x2, UV lamp x2
Optional Accessory	Base stand
Internal Size	640Wx550Dx700H mm
External Size	700Wx620Dx1150H mm
Package Size	840Wx760Dx1400H mm
Gross Weight	100kg
Consumption	300W
Power Supply	AC220V±10%, 50/60Hz; 110V±10%, 60Hz

LABSTAC

Labstac LLC

82 Wendell Avenue, STE 100, Pittsfield, MA, 01201, USA
Email: contact@m.labstac.com | Website: labstac.com