

LABSTAC

COMPOUNDING HOOD LAF38-660MC



labstac.com

COMPOUNDING HOOD LAF38-660MC

It has compact desktop design required for operations in an ultra clean, dust free environment. Used for a wide range of applications according to users need.

Used in Research, Pharmaceutical, Medical, Manufacturing areas, Electronic setors, Industrial sectors, Laboratory, Healthcare.

Also known as Desktop Laminar Air flow, Benchtop Laminar Air Flow, Laminar Flow Cabinet, Clean Bench, Laboratory Laminar Flow, Laboratory Laminar Air Flow, Tissue Culture Hood, Laminar Air Flow Cabinet, Minimal-Turbulence Air Flow, Laminar Flow Cabinet, Laminar Flow Hood, Laminar Flow.

LAF38-660MC COMPOUNDING HOOD



SPECIFICATIONS

Model	LAF38-660MC
Type	Desktop Laminar Flow
Airflow Velocity	0.3~0.8m/s
Filter	Active Carbon Filter, HEPA Filter
Pre-Filter	/
Max Opening	660mm
Main Body Material	Cold-rolled steel with anti-bacteria power coating
Work Table Material	Solid physicochemical steel plate
Front Window	Manual, acrylic material
UV Lamp	15W x1 Emission of 253.7 nanometers
LED Lamp	12W x1
Display	LED Display
Noise	≤60dB
Standard Accessory	Active carbon filter, HEPA filter, LED lamp x1, 4 meters PVC exhaust duct, Diameter: 250mm.
Optional Accessory	Base stand, UV lamp x2
Internal Size	1140Wx550Dx700H mm
External Size	1200Wx620Dx1150H mm
Package Size	1340Wx740Dx1360H mm
Gross Weight	190kg
Consumption	400W
Power Supply	AC220V±10%, 50/60Hz; 110V±10%, 60Hz

LABSTAC

Labstac LLC

82 Wendell Avenue, STE 100, Pittsfield, MA, 01201, USA
Email: contact@mail.labstac.com | Website: labstac.com