

AUTOMATIC SEALING AND CAPPING MACHINE LIH11-210RT



AUTOMATIC SEALING AND CAPPING MACHINE

LIH11-210RT

Automatic Sealing and Capping Machine is specifically designed to speed up the process of packaging of your product but also ensure the sterility of the product and that the product does not get contaminated

Used in Food Industry, Beverage Industry, Bio-medicine, Inspection institutions, Pharmaceuticals.

Also known as Screw on capping machine.

LIH11-210RT AUTOMATIC SEALING AND CAPPING MACHINE

4.3-inch touch screen, easy to operate

Real-time observation of the operating state of the instrument, can be used as a single machine

Customize the sealing temperature as required

Complete the whole process automatically, with stable results and good repeatability

Suitable for a variety of heat sealing films

Multifunctional limit column to prevent heat seal film offset

With emergency stop function and standby function



SPECIFICATIONS

Model	LIH11-210RT
Temp. Range	RT~210°C
Temp. Precision	±1°C
Heating Rate	Heat to 170°C in 240 seconds
Cooling Keep	When sealing the film, the heating body drops temperature :≤3°C, and rises to the preset temperature within 20s.
Sealing Membrane Time	0.1~15 s
Film Sealing Time Accuracy	0.1 s
Pressure Level	1~5 level can be set, multi-level adjustable
Plate Type	Deep well plate, PCR plate, ELISA plate, etc. Standard: PCR plate adapter Optional: ELISA plate adapter, 384 well plate adapter
External Size	325x176x262 mm
Package Size	530x230x290 mm
Net/Gross Weight	10.5/11.5kg
Consumption	400 W
Power Supply	Standard: 220V 50/60Hz Optional: 110V 50/60Hz



Labstac LLC

82 Wendell Avenue, STE 100, Pittsfield, MA, 01201, USA
Email: contact@labstac.com | Website: labstac.com