

MULTI-PARAMETER ANALYZER MET101-078



MULTI-PARAMETER ANALYZER MET101-078

Multi-parameter Analyzer simultaneously measures Ion, Conductivity, Dissolved Oxygen, Temperature that otherwise requires four different meters. With the appropriate probes installed, it can also simultaneously measure several or one parameters.

MET101-078 MULTI-PARAMETER ANALYZER



Product Image Coming Soon

SPECIFICATIONS

Model	MET101-078
DC Voltage	
60 Mv/600 mV/6 V/60 V	± (0.5%+3)
600 V	± (0.5%+3)
AC Voltage	
60 mV/600 mV/6 V/60 V/600 V	± (0.8%+3)
DC Current	
600 µA/6 mA/60 mA/600 mA	± (0.8%+3)
6 A/10 A	± (1.2%+3)
AC Current	
600 µA/6 mA/60 mA/600 mA	± (0.1%+3)
6 A/10 A	± (1.5%+3)
Resistance	
600 Ω/6 kΩ/60 kΩ/600 kΩ/6 MΩ	± (1.2%+5)
60 MΩ	± (2.0%+5)
Capacitance	
10 nF/100 nF/1 µF/10 µF/100 µF	± (3.0 % + 5)
	± (4.0 % +5)
100 mF	± (5.0 % +5)
Frequency	
10 Hz ~10 MHz	± (1.0%+5)
Duty	
1 % ~ 99 %	± (3.0 % +5)
Display	6000
Auto Range	Yes

Bargraph Display	Yes
Data Hold	Yes
VFD Measurement	Yes
Relative Measurement	Yes
MAX/MIN Measurement	Yes
Diode Test	Yes
Continuity	Yes
NCV Non-Contact Voltage Detection	Yes
Live Line Voltage Detection	Yes
Back Light	Yes
Power Supply	2x 1.5 VAAA
Weight	268.5
Size	166x78x48 mm
Safety Standard/Rating	EN61010-1,EN61010-2-033,EN61326,CAT.III 600 V



Labstac LLC

82 Wendell Avenue, STE 100, Pittsfield, MA, 01201, USA
 Email: contact@mail.labstac.com | Website: labstac.com