LABSTAC

MULTI-PARAMETER ANALYZER MET101-083

labstac.com

MULTI-PARAMETER ANALYZER MET101-083

Multi-parameter Analyzer simultaneously measures Ion, Conductivity, Dissolved Oxygen, Temperature that otherwise requires four different meters. With the appropriate probes installed, it can also simultaneously measure several or one parameters.

MET101-083 MULTI-PARAMETER ANALYZER

SPECIFICATIONS

Model	MET101-083
DC Voltage	
6 V/60 V/600 V	± (0.8%+3)
AC Voltage	
60 Mv/600 mV/6 V/60 V/600 V/750 V	± (0.8%+3)
DC Current	
600 mA	± (1.0%+3)
AC Current	
600 mA	± (1.5%+3)
Resistance	
6 kΩ/60 kΩ/600 kΩ	± (1.0%+3)
6 MΩ/10 MΩ	± (1.2%+5)
Capacitance	
60 nF/600 nF/6 μF/60 μF/600 μF/6 mF	± (1.0%+5)
Frequency	
30 ~1000 Hz	± (0.5%+2)
Temperature	
- 20 °C ~ 1300 °C	± (1.0%+3)
- 4 °F ~ 2372 ° F	± (1.0 % + 3)
Display	6000 Counts
Auto Range	Yes
Bargraph Display	Yes
Transistor	Yes
Continuity	Yes
NCV	Yes

hFE	Yes
Live Test	Yes
Data Hold	Yes
Work Light	Yes
Back Light	Yes
Auto Power Off	Yes
Power Supply	3x 1.5V AAA Batteries
Weight	Approx.250 g
Size	169x83x53 mm
Safety Standard/Rating	EN61010-1,EN61010-2-033, EN61326,CAT.III 600 V

Labstac LLC
82 Wendell Avenue, STE 100, Pittsfield, MA, 01201, USA
Email: contact@labstac.com | Website: labstac.com