

# THERMAL IMAGING CAMERA METERS MET11-15



# THERMAL IMAGING CAMERA METERS MET11-15

Thermal imaging cameras are non-contact devices used to capture detailed images in low-light environments. It works by detecting infrared energy (heat) which interprets temperature as colour and converting it into an image in real-time. Red and yellow colours depicts warmer areas and purple or blue colours depict cooler areas.

## MET11-15 THERMAL IMAGING CAMERA METERS



### SPECIFICATIONS

Model	MET11-15
Display	2.4 " Color display
Resolution	60x60
Total pixels	3600
FOV/Shortest focal length	20°x20°/0.5 m
Thermal sensitivity	0.15 °C
Measuring mode	Infrared focal plane measuring temperature
Temperature range	-20 °C~300 °C (-4°F~572°F)
Measuring accuracy	± 2% digital/± 2°C
Wavelength range	8~14 μm
Image frequency	6 Hz
Emissivity	0.1-1.0 Adjustable
Focus Mode	Fixed
Palette	Iron colon,rainbow,black and white
Image Storage	card(4G)
File Format	bmp
Set control	unit adjustment/Language/date time /Format/automatic shutdown
Battery type	4*AA alkaline batteries
Operating temperature	5°C~40°C
Storage temperature	- 20 °C~ 50 °C
Humidity	10% RH to 80% RH
Vibration	2G,IEC 60068-2-6
Size	230x80x52 mm
Weight	320 g
Waterproof rating	IP65

***LABSTAC***

**Labstac LLC**

82 Wendell Avenue, STE 100, Pittsfield, MA, 01201, USA  
Email: [contact@mail.labstac.com](mailto:contact@mail.labstac.com) | Website: [labstac.com](http://labstac.com)