

# CONDUCTIVITY METER MET31-100



# CONDUCTIVITY METER MET31-100

Conductivity meter is an instrument that measures the amount of electric conductivity or current in a solution. The conductance can be measured by applying an alternating electrical current to the two electrodes present in the solution, after which the cations move to the negative electrode and the anions move to the positive electrode. This movement ultimately leads the solution to be conductive.

## MET31-100 CONDUCTIVITY METER



### SPECIFICATIONS

Model	MET31-100
Conductivity	
Range	0.00 $\mu\text{S}/\text{cm}$ to 100 $\text{mS}/\text{cm}$
Resolution	0.01 $\mu\text{S}/\text{cm}$ minimum; changed with range
Accuracy	$\pm 1.5\%$ FS
Reference Temperature	25 $^{\circ}\text{C}$
Measurement	
Reading Mode	Continuous
Reading Prompts	Reading, Stable
Temp. Compensation	MTC
Inputs	
pH Electrode	BNC(Q9)
Conductivity Probe	5-pin aviation connector
Display Options	
Backlight	Yes
Auto Shutdown	300, 600, 1200, 1800, 3600 sec., off
IP Rating	IP54
General	
Power	AC Adapter, 100-240 V AC input, DC9 V output
Dimensions	200x160x63 mm
Weight	600 g (1.32 lb)



**Labstac LLC**

82 Wendell Avenue, STE 100, Pittsfield, MA, 01201, USA  
Email: [contact@labstac.com](mailto:contact@labstac.com) | Website: [labstac.com](http://labstac.com)