

PH/ION METER MET51-135



PH/ION METER MET51-135

An ion meter is a device which with the aid of electrochemical activity of ion electrodes measures the concentration of ions in a solution. It works by the means of selective ion electrodes and measuring ion activity capability of sensitive membrane of a measuring devices. A sensor electrode and a reference electrode are used to measure the ion concentration in a solution.

MET51-135 PH/ION METER



SPECIFICATIONS

Model	MET51-135
pH	
Range	-2.000 to 20.000 pH
Resolution	0.1, 0.01, 0.001 pH
Accuracy	± 0.002 pH
Calibration Points	Up to 8
Standard Customization	Yes
Calibration Reminder	Yes
Standard Recognition	USA, NIST, MERK, JIS, GB and DIN buffers
Slope Limit	Yes
mV/ORP	
Range	- 2000.00 to 2000.00 mV
Resolution	0.1, 0.01 mV
Accuracy	±0.1 mV or ±0.03 % of reading whichever is greater
EH ORP Mode	Yes
ORP Calibration Points	1 custom point (relative mV)
pX	
Range	- 2.000 to 20.000 pX
Resolution	0.1, 0.01, 0.001 pX
Accuracy	±0.002 pX
Calibration Points	Up to 6
ISE	
Range	1 E-9 to 9.999 E9
Unit	mol/L, mmol/L, g/L, mg/L, µg/L

Resolution	Up to 4 significant digits
Accuracy	± 0.3 %
Calibration Points	Up to 8
Temperature	
Range	- 10 to 135 °C, 14 to 275 °F
Unit	°C, °F
Resolution	0.1
Relative Accuracy	± 0.2
Measurement	
Reading Mode	AutoRead(Fast, Medium,Slow), Timed, Continuous
Reading Prompts	Reading, Stable, Locked
Data Management	
Data Storage	1000 Groups
GLP Features	Yes
Inputs	
pH Electrode	BNC(Q9)
Temp./DO Probe	4-pin aviation connector
Outputs	
USB	USB 2.0 flash memory device, PC,scanner
Bluetooth	printer
Display Options	
Backlight	Yes
Auto Shut-down	300, 600, 1200, 1800, 3600 sec, off
IP Rating	IP65
General	
Power	AC Adapter, 100-240 V AC input, DC 5 V output
Dimensions	90x255x40 mm
Weight	500 g(1.1 lb)



Labstac LLC

82 Wendell Avenue, STE 100, Pittsfield, MA, 01201, USA
 Email: contact@mail.labstac.com | Website: labstac.com