

# PH/ION METER MET51-300



# PH/ION METER MET51-300

An ion meter is a device which with the aid of electrochemical activity of ion electrodes measures the concentration of ions in a solution. It works by the means of selective ion electrodes and measuring ion activity capability of sensitive membrane of a measuring devices. A sensor electrode and a reference electrode are used to measure the ion concentration in a solution.

## MET51-300 PH/ION METER



### SPECIFICATIONS

Model	MET51-300
pH	
Range	-2.00 to 20.00 pH
Resolution	0.1, 0.01 pH
Accuracy	± 0.01 pH
Calibration Points	Up to 5
Standard Customization	Yes
Standard Recognition	NIST, GB and DIN buffers
mV	
Range	-2000.00 to 2000.00 mV
Resolution	0.1
Accuracy	± 0.3 mV or ± 0.1 %
pX	
Range	- 2.00 to 20.00
Resolution	0.1, 0.01 pX
Accuracy	±0.02 pX
Calibration Points	Up to 5
ISE	
Range	1E-9 to 9.999E9
Unit	mol/L, mmol/L, g/L, mg/L, µg/L, ppm
Resolution	Up to 4 significant digits
Accuracy	± 0.5 %
Calibration Points	Up to 5
Temperature	

Range	-5 to 110 °C, 23 to 230 °F
Unit	°C, °F
Resolution	0.1
Relative Accuracy	± 0.2
Measurement	
Reading Mode	AutoRead( Fast, Medium, Slow), Timed, Continuous
Reading Prompts	Reading, Stable, Locked
Temp. Compensation	ATC, MTC
Data Management	
Data Storage	1000 results each
GLP Features	Yes
Inputs	
pH Electrode	BNC(Q9)
Temp./DO Probe	4-pin aviation connector
Outputs	
USB	USB 2.0 flash memory device, PC,scanner
Display Options	
Backlight	Yes
Auto Shutdown	300, 600, 1200, 1800, 3600 sec, off
IP Rating	IP65
Yes	General: Power
General	
Dimensions	90x255x40 mm
Weight	500 g(1.1 lb)



**Labstac LLC**

82 Wendell Avenue, STE 100, Pittsfield, MA, 01201, USA  
 Email: [contact@mail.labstac.com](mailto:contact@mail.labstac.com) | Website: [labstac.com](http://labstac.com)