

GLOSS METER MET91-040



GLOSS METER MET91-040

A glossmeter measures the specular reflection (gloss) of a surface. It determines the gloss by projecting a beam of light onto a surface at a fixed angle and intensity then measures the amount of reflected light at an opposite but equal angle.

MET91-040 GLOSS METER



SPECIFICATIONS

Model	MET91-040
Measuring Angle	60°
Measuring Area (mm)	60°:9X15
Measuring Range	60°:0~200 GU
Division Value	1 GU
Measuring Time	0.5 s
Repeatability	0~100GU:±0.5GU 100-200GU: ±0.5G U %
Accurate	second grade requirements of gloss meter
Auto Power-off Time	30 s
Language	Chinese English
Display	2.3 inch black and white screen
Size	160x52x84 mm
Weight	About 300 g
Power Supply	1 pc dry-cell battery(can measure 10000 times) or use USB Charge
Interface	USB
Operation Temperature Range	0~40 °C (32~104 °F)
Storage Temperature Range	- 20~50 °C (-4~122°F)
Humidity Range	< 85% RH, without condensation
Standard Accessories	User manual, calibration plate,USB cable, user manual, QC software (Download official website) calibration plate,user manual
Optional Accessories	Miniature printer

LABSTAC

Labstac LLC

82 Wendell Avenue, STE 100, Pittsfield, MA, 01201, USA
Email: contact@mail.labstac.com | Website: labstac.com