

3D ROTATING MIXER MIX11-40



3D ROTATING MIXER MIX11-40

DC brushless motor provides reliable and quiet running, maintenance free and can be used in cold rooms or in incubators, Majorly used in Industrial, Clinical Laboratories, Academic Facilities, Environmental Applications, Food Technology and Wastewater Facilities.

Used in Industrial, Clinical Laboratories, Academic Facilities, Environmental Applications, Food Technology, Wastewater Facilities.

Also known as Tube Rotator, Rotator, Laboratory Rotator.

MIX11-40 3D ROTATING MIXER

Unique combination of adjustable rotating frame.

A variety of rotation modes, from mild type to somersault type rotation mode.

With reciprocating oscillation function from 20 angel to 99 angle.

Widely used in molecular biology, histo-chemistry, bio-chemistry, clinical applications, etc.

Provide three types of rotating frame.



SPECIFICATIONS

Model	MIX11-40
Speed Range	10 rpm ~40 rpm
Reciprocating Swing Angle Range	20°~99° (Adjustable)
Time Range	1s~999min/Continuously
Voltage	AC 100 ~230V, 50/60Hz
Power	4 W
Fuse	250V, 1A, Φ5x20
Dimension	240x145x210 mm
Net Weight	1.2 kgs

LABSTAC

Labstac LLC

82 Wendell Avenue, STE 100, Pittsfield, MA, 01201, USA

Email: contact@labstac.com | Website: labstac.com