

MULTI-TUBE VORTEX MIXER MIX35-25M



MULTI-TUBE VORTEX MIXER MIX35-25M

Constructed of rugged, corrosion-resistant materials, the instruments endure heavy everyday usage. The ergonomic low profile design makes everyday vortexing comfortable for the user. Unnecessary movement has been avoided during use due to robust die-cast body.

Used in Mixing, Laboratory, Research, Medical.

Also known as Laboratory Vortex Mixer.

MIX35-25M MULTI-TUBE VORTEX MIXER

Max capacity can process 50 samples at the same time to make the experiment more convenient and efficient

Microprocessor control, simplistic designed appearance, LED displays the speed and time

Friendly program designed, built-in short mix, timing operation, impulse and continuous modes. Operation stable and silent

A foam tube frame and tray pad configured at random. Various types of foam tube frames and pads to choose. tube frames and pads to choose



SPECIFICATIONS

Model	MIX35-25M
Speed Range	500-2500 rpm
Speed Accuracy	±1 rpm
Shaking Orbit	4 mm
Time Range	1 s~9999 min
Interval timing between impulse	1~10 s
Timing set for impulse working	1 s~99 min 59 s
Max Load	5 kgs
Cover Plate Size	W.184 x L.311 mm
Voltage	AC 100~230 V, 50/60Hz
Power	60 W
Fuse	250 V, 1 A, φ5 x 20
Dimension	W.250 x D.426 x H.480 mm
Net Weight	15 kgs

OPTIONAL ACCESSORIES

Accessory Code	Name	Dimension	Number of Holes
3000605005	Tube frame	245 x 132 x 45 mm	
3000605006	Tube frame	245 x 132 x 45 mm	
3000605007	Tube frame	245 x 132 x 45 mm	
3000605008	Tube frame	245 x 132 x 45 mm	
3000605009	Tube frame	245 x 132 x 45 mm	

3000605010	Tube frame	245 x 132 x 45 mm	
3000605011	Tray pad set	305 x 178.5 x 25 mm	
3000605012	Φ38mm foam tube frame (suit for 100ml tube)	245x132x45 mm	10
3000605013	Acrylic tube frame Φ11mm (suit for 1.5/2.0ml tube)	169x84x41 mm	40



Labstac LLC

82 Wendell Avenue, STE 100, Pittsfield, MA, 01201, USA

Email: contact@labstac.com | Website: labstac.com