

VORTEX MIXER MIX37-25



VORTEX MIXER MIX37-25

Constructed of rugged, corrosion-resistant materials, the instruments endure heavy everyday usage. The ergonomic low profile design makes everyday vortexing comfortable for the user. Unnecessary movement has been avoided during use due to robust die-cast body.

Used in Mixing, Laboratory, Research, Medical.

Also known as Laboratory Vortex Mixer.

MIX37-25 VORTEX MIXER

Touch operation or continuous mode

Used for various mixing applications with optional adapters

Various adapters fit for different tubes

Specially designed vacuum suction foot for body stability

Robust aluminum-cast construction



SPECIFICATIONS

Model	MIX37-25
Speed Range	25000 rpm
Permissible Ambient Temperature	5-40°C
Permissible Relative Humidity	80% RH
Orbital Diameter	4 mm
53	Motor rating output [W]
Operation	Continuous/ touch operation
Overall Dimension	127Wx130Hx160Dmm
Motor Type	Shaded pole motor
Protection Class	IP21
Weight	3.5 kg
Power	60 W
Power Supply	110-120 V/220-230 V, 50/60 Hz

OPTIONAL ACCESSORIES

Accessory Code	Name	Description
3000807005	Rubber vacuum suction foot with screw; 1pc	
3000807006	Platform pad	For <φ99mm tubes and small vessels
3000807007	Standard top cup	For <φ30mm tubes and small vessels

Accessory Code	Name	Description
3000807010	Tube adapter	For 12 holes test tubes; φ12mm ; used with Mx1027/ Mx1026/PS1.1
3000807011	Tube adapter	For 8 holes test tubes; φ16mm; used with Mx1027/ Mx1026/PS1.1

3000807008	Tube adapter	For 48 holes test tubes; φ6mm; used with Mx1027/ Mx1026/PS1.1
3000807009	Tube adapter	For 15 holes test tubes; φ10mm; used with Mx1027/ Mx1026/PS1.1

3000807012	Tube adapter	For 8 holes test tubes; φ20mm; used with Mx1027/ Mx1026/PS1.1
3000807013	Universal top plate	100mm plate attachment ; free of Rubber vacuum suction foot (18900158; 4pcs)
3000807014	Tube holding rod	Used with Mx1028 to Mx1032

LABSTAC

Labstac LLC

82 Wendell Avenue, STE 100, Pittsfield, MA, 01201, USA

Email: contact@labstac.com | Website: labstac.com