

MICROWAVE DIGESTER MWD19-18



MICROWAVE DIGESTER MWD19-18

When a sudden over-pressure scenario arises, an automatic vent and self-resealing structure rapidly release pressure and reseal. Mechanism for monitoring pressure and temperature without contact. It can edit and save 255 different sorts of programmes depending on what the user needs.

Used in Pharmaceutical Analysis, Agricultural, Environmental Analysis, Biological Sciences.

Also known as Microwave Digester, Microwave Extraction.

MWD19-18 MICROWAVE DIGESTER

Automatic vent and self-resealing structure release pressure and instantly reseal when a sudden over-pressure situation occurs.

Contact-less Temperature and Pressure Monitoring System.

With Vessel Quantity of 18, it can edit and store 255 types of programs according to user's requirements.



SPECIFICATIONS

Model	MWD19-18	
Vessel Quantity	18	
Vessel Volume	100mL	
Vessel material	Inner.Imported TFM Outer.Imported PEEK+Glass Fiber	
Temperature Monitoring System	Contactless IR sensor	
Temperature Control	Scanning control of each vessel	
Temperature Control Range	50-400 °C	
Maximum Working Temperature	250 °C	
Temperature Control Accuracy	±0.3 ℃	
Inner Vessel Temperature Limit	300 °C	
Pressure Testing	Contactless pressure sensor	
Pressure Control range	0-10MPa	
Pressure Control Accuracy	0.01MPa	
Maximum Working Pressure	6 MPa	
Microwave Frequency	2450Hz	
Rotation Mode	360° Continuous Rotation	
Microwave Leak	<5mw/cm2	
Microwave Power	0-2000W Adjustable/ 0-3000W Adjustable	

labstac.com

2

OPTIONAL ACCESSORIES

Accessory Code	Name	Sample quantity	Aperture and Hole depth	Temperature Control Range
7500513005	Heating Blocks	20	Ф 41x150mm	Room Temperature -250°C



Labstac LLC

82 Wendell Avenue, STE 100, Pittsfield, MA, 01201, USA Email: contact@labstac.com | Website: labstac.com