

MICROWAVE DIGESTER MWD20-40



MICROWAVE DIGESTER MWD20-40

When a sudden over-pressure scenario arises, an automatic vent and self-resealing structure rapidly release pressure and reseal. Mechanism for monitoring pressure and temperature without contact. It can edit and save 255 different sorts of programmes depending on what the user needs.

Used in Pharmaceutical Analysis, Agricultural, Environmental Analysis, Biological Sciences.

Also known as Microwave Digester, Microwave Extraction.

MWD20-40 MICROWAVE DIGESTER

Special Designed Sample Digestion Vessel.

Contact-less Temperature and Pressure Monitoring System.

With vessel quantity of 40, It can edit and store 255 types of programs according to user's requirements.



SPECIFICATIONS

Model	MWD20-40
Vessel Quantity	40
Vessel Volume	50mL
Vessel material	Inner.Imported TFM Outer.Imported PEEK Glass Fiber
Temperature Monitoring System	Contactless IR sensor
Temperature Control	Scanning control of each vessel
Temperature Control Range	50-400 °C
Maximum Working Temperature	250 °C
Temperature Control Accuracy	±0.3 °C
Inner Vessel Temperature Limit	300 °C
Pressure Testing	Contactless pressure sensor
Pressure Control range	0-10MPa
Pressure Control Accuracy	0.01MPa
Maximum Working Pressure	6 MPa
Microwave Frequency	2450Hz
Rotation Mode	360° Continuous Rotation
Microwave Leak	<5mw/cm2
Microwave Power	0-3000W Adjustable

OPTIONAL ACCESSORIES

Accessory Code	Name	Sample quantity	Aperture and Hole depth	Temperature Control Range
7500514005	Heating Blocks	20	Φ 32x118mm	Room Temperature -250°C

LABSTAC

Labstac LLC

82 Wendell Avenue, STE 100, Pittsfield, MA, 01201, USA

Email: contact@labstac.com | Website: labstac.com