

DRYING OVEN OVE074-040



DRYING OVEN OVE074-040

OVE074-040 DRYING OVEN

Polished stainless-steel chamber, semicircular arcs at corners for easy cleaning, and the space between the shelves in the chamber is adjustable

Auto-controller of fan speed to prevent damage to the samples

Large LCD screen to display more data at same time

Self-check function easy to identify problems

Over temperature and temperature difference alarms

There is a 25mm instruction connection hole on the left side of the chamber for easy testing operation and temperature

Programmable controller: 7 periods 63 steps, 0~5999min for each periods, fan speed 0 to 100% adjustable

Independent audible and visible temperature-limiting alarm system ensures experiments run safely

RS485 connector can connect computer and printer to record the parameters and the variations of temperature



SPECIFICATIONS

| | |
|------------------------|--------------------------|
| Model | OVE074-040 |
| Capacity | 40 L |
| Electrical requirement | 220 V 50 Hz |
| Controller | Programmable LCD display |
| Power Consumption | 850 W |
| Temperature Range | RT +10 - 250°C |
| Display Resolution | 0.1°C |
| Temperature Stability | ±1°C |
| Temperature Uniformity | ±2.5% |
| Shelves | 2 pcs |
| Interior Dimension | 350Wx300Dx400H mm |
| Exterior Dimension | 505Wx655Dx600H mm |
| Timing Range | 0~5999 min |

LABSTAC

Labstac LLC

82 Wendell Avenue, STE 100, Pittsfield, MA, 01201, USA

Email: contact@labstac.com | Website: labstac.com