

DRYING OVEN OVE074-080



DRYING OVEN OVE074-080

OVE074-080 DRYING OVEN

Polished stainless-steel chamber, semicircular arcs at corners for easy cleaning, and the space between the shelves in the chamber is adjustable

Auto-controller of fan speed to prevent damage to the samples

Large LCD screen to display more data at same time

Self-check function easy to identify problems

Over temperature and temperature difference alarms

There is a 25mm instruction connection hole on the left side of the chamber for easy testing operation and temperature

Programmable controller: 7 periods 63 steps, 0~5999min for each periods, fan speed 0 to 100% adjustable

Independent audible and visible temperature-limiting alarm system ensures experiments run safely

RS485 connector can connect computer and printer to record the parameters and the variations of temperature



SPECIFICATIONS

Model	OVE074-080
Capacity	80 L
Electrical requirement	220 V 50 Hz
Controller	Programmable LCD display
Power Consumption	1100 W
Temperature Range	RT +10 - 250°C
Display Resolution	0.1°C
Temperature Stability	±1°C
Temperature Uniformity	±2.5%
Shelves	2 pcs
Interior Dimension	400Wx320Dx550H mm
Exterior Dimension	550Wx660Dx750H mm
Timing Range	0~5999 min

LABSTAC

Labstac LLC

82 Wendell Avenue, STE 100, Pittsfield, MA, 01201, USA

Email: contact@labstac.com | Website: labstac.com