

# VACUUM DRYING OVEN OVE077-090A



# VACUUM DRYING OVEN OVE077-090A

## OVE077-090A VACUUM DRYING OVEN

Microprocessor controller

Dual layer tempered glass door for clear observation

Minimum heating time 50% less than traditional vacuum oven

Interior chamber made from stainless steel with a mirror polished finish making for easy cleaning

Standard with vacuum pump

Direct heating and control by shelves: Each shelf has a separate temperature sensor, can be independently displayed and controlled temperature in setting, monitoring and timing, more accurate and stable



## SPECIFICATIONS

Model	OVE077-090A
Capacity	90 L
Electrical requirement	AC 220 V 50 HZ
Controller	LED display
Power Consumption	1350 W
Temperature range	RT+10 - 200°C
Display Resolution	0.1
Temperature Stability	±1°C
Vacuum Degree	133 Pa
Ambient Temperature	+5 - 40°C
Interior Dimension	450Wx450Dx450H mm
Exterior Dimension	610Wx590Dx1350H mm
Shelves	2 pcs
Chamber Material	304 Stainless steel

# LABSTAC

**Labstac LLC**

82 Wendell Avenue, STE 100, Pittsfield, MA, 01201, USA

Email: [contact@labstac.com](mailto:contact@labstac.com) | Website: [labstac.com](http://labstac.com)