

VACUUM DRYING OVEN OVE077-215A



VACUUM DRYING OVEN OVE077-215A

OVE077-215A VACUUM DRYING OVEN

Microprocessor controller

Dual layer tempered glass door for clear observation

Minimum heating time 50% less than traditional vacuum oven

Interior chamber made from stainless steel with a mirror polished finish making for easy cleaning

Standard with vacuum pump

Direct heating and control by shelves: Each shelf has a separate temperature sensor, can be independently displayed and controlled temperature in setting, monitoring and timing, more accurate and stable



SPECIFICATIONS

Model	OVE077-215A
Capacity	215 L
Electrical requirement	AC 220 V 50 HZ
Controller	LED display
Power Consumption	2100 W
Temperature range	RT+10 - 200°C
Display Resolution	0.1
Temperature Stability	±1°C
Vacuum Degree	133 Pa
Ambient Temperature	+5 - 40°C
Interior Dimension	560Wx600Dx640H mm
Exterior Dimension	720Wx8200Dx1750H mm
Shelves	3 pcs
Chamber Material	304 Stainless steel

LABSTAC

Labstac LLC

82 Wendell Avenue, STE 100, Pittsfield, MA, 01201, USA

Email: contact@labstac.com | Website: labstac.com