

# VACUUM DRYING OVEN OVE078-125



# VACUUM DRYING OVEN OVE078-125

## OVE078-125 VACUUM DRYING OVEN

Microprocessor controller

Dual layer tempered glass door for clear observation

Minimum heating time 50% less than traditional vacuum oven

Interior chamber made from stainless steel with a mirror polished finish making for easy cleaning

Standard with vacuum pump

Provides programmability for 7 periods and 9 steps for each period making for a total of 63 programmable step



## SPECIFICATIONS

Model	OVE078-125
Capacity	125 L
Electrical requirement	AC 220 V 50 HZ
Controller	LCD Programmability controller
Power Consumption	2050 W
Temperature range	RT+ 10 - 200°C
Display Resolution	0.1
Temperature Stability	±1°C
Vacuum Degree	133 Pa
Ambient Temperature	+5 - 40°C
Interior Dimension	500Wx500Dx500H mm
Exterior Dimension	660Wx640Dx1400H mm
Shelves	3 pcs
Chamber Material	304 Stainless steel

# LABSTAC

**Labstac LLC**

82 Wendell Avenue, STE 100, Pittsfield, MA, 01201, USA

Email: [contact@labstac.com](mailto:contact@labstac.com) | Website: [labstac.com](http://labstac.com)