

VACUUM DRYING OVEN OVE079-032



VACUUM DRYING OVEN OVE079-032

OVE079-032 VACUUM DRYING OVEN

Programmable vacuum cycle
LCD vacuum degree window
Suitable for drying thermo-sensitive material
Shorter drying time for sample that does not dry easily
Dual layer tempered glass door for clear observation
Fully automatic electromagnetism controlled vacuum
Minimum heating time 50% less than traditional vacuum oven



SPECIFICATIONS

Model	OVE079-032
Capacity	32 L
Electrical requirement	AC 220 50 HZ
Temperature Range	RT+10 - 200°C
Display Resolution	0.1°C
Temperature Stability	±1°C
Vacuum Gauge	Digital Display
Vacuum Degree	133 Pa
Vacuum Sensor	Resistance silicon tube pressure sensor
Vacuum Control Range	10 - 100000 Pa
Power Consumption	1200 W
Interior Dimension	320Wx320Dx320H mm
Exterior Dimension	550Wx490Dx1240H mm
Shelves	2 pcs
Chamber Material	304 Stainless steel

LABSTAC

Labstac LLC

82 Wendell Avenue, STE 100, Pittsfield, MA, 01201, USA

Email: contact@labstac.com | Website: labstac.com