

VACUUM DRYING OVEN OVE079-064



VACUUM DRYING OVEN OVE079-064

OVE079-064 VACUUM DRYING OVEN

Programmable vacuum cycle
LCD vacuum degree window
Suitable for drying thermo-sensitive material
Shorter drying time for sample that does not dry easily
Dual layer tempered glass door for clear observation
Fully automatic electromagnetism controlled vacuum
Minimum heating time 50% less than traditional vacuum oven



SPECIFICATIONS

Model	OVE079-064
Capacity	64 L
Electrical requirement	AC 220 50 HZ
Temperature Range	RT+10 - 200°C
Display Resolution	0.1°C
Temperature Stability	±1°C
Vacuum Gauge	Digital Display
Vacuum Degree	133 Pa
Vacuum Sensor	Resistance silicon tube pressure sensor
Vacuum Control Range	10 - 100000 Pa
Power Consumption	1800 W
Interior Dimension	400Wx400Dx400H mm
Exterior Dimension	600Wx570Dx1390H mm
Shelves	3 pcs
Chamber Material	304 Stainless steel

LABSTAC

Labstac LLC

82 Wendell Avenue, STE 100, Pittsfield, MA, 01201, USA

Email: contact@labstac.com | Website: labstac.com