

VACUUM DRYING OVEN OVE079-215



VACUUM DRYING OVEN OVE079-215

OVE079-215 VACUUM DRYING OVEN

- Programmable vacuum cycle
- LCD vacuum degree window
- Suitable for drying thermo-sensitive material
- Shorter drying time for sample that does not dry easily
- Dual layer tempered glass door for clear observation
- Fully automatic electromagnetism controlled vacuum
- Minimum heating time 50% less than traditional vacuum oven



SPECIFICATIONS

Model	OVE079-215
Capacity	215 L
Electrical requirement	AC 220 50 HZ
Temperature Range	RT+ 10 - 200°C
Display Resolution	0.1°C
Temperature Stability	±1°C
Vacuum Gauge	Digital Display
Vacuum Degree	133 Pa
Vacuum Sensor	Resistance silicon tube pressure sensor
Vacuum Control Range	10 - 100000 Pa
Power Consumption	2100 W
Interior Dimension	560Wx600Dx640H mm
Exterior Dimension	720Wx820Dx1750H mm
Shelves	3 pcs
Chamber Material	304 Stainless steel

LABSTAC

Labstac LLC

82 Wendell Avenue, STE 100, Pittsfield, MA, 01201, USA
Email: contact@labstac.com | Website: labstac.com