

# VACUUM DRYING OVEN OVE079-913



# VACUUM DRYING OVEN OVE079-913

## OVE079-913 VACUUM DRYING OVEN

- Programmable vacuum cycle
- LCD vacuum degree window
- Suitable for drying thermo-sensitive material
- Shorter drying time for sample that does not dry easily
- Dual layer tempered glass door for clear observation
- Fully automatic electromagnetism controlled vacuum
- Minimum heating time 50% less than traditional vacuum oven



### SPECIFICATIONS

Model	OVE079-913
Capacity	913 L
Electrical requirement	AC 380 V 50 HZ
Temperature Range	RT+10 - 200°C
Display Resolution	0.1°C
Temperature Stability	±1°C
Vacuum Gauge	Digital Display
Vacuum Degree	133 Pa
Vacuum Sensor	Resistance silicon tube pressure sensor
Vacuum Control Range	10 - 100000 Pa
Power Consumption	5600 W
Interior Dimension	750Wx1160Dx1050H mm
Exterior Dimension	1400Wx1395Dx2010H mm
Shelves	5 pcs
Chamber Material	304 Stainless steel

**LABSTAC**

**Labstac LLC**

82 Wendell Avenue, STE 100, Pittsfield, MA, 01201, USA  
Email: [contact@labstac.com](mailto:contact@labstac.com) | Website: [labstac.com](http://labstac.com)