

LARGE CAPACITY PIPETTE PIP14-01100E



LARGE CAPACITY PIPETTE PIP14-01100E

Single Channel Pipette is the new standard for microliter measurements. It is suitable for pipetting from 0.1ml to 100ml. Can control the whole process from absorb fluid to pipetting with two buttons. It is top of the line micropipette that is ergonomically designed and easily adjustable. They are commonly used in laboratory, research, chemistry, biology, forensic, pharmaceutical, and drug discovery labs to transfer small quantities of liquid.

Used in Environmental Sciences, Laboratory, Research, Liquid Handling Task, Institutes, Pharmaceutical, Industrial, Microbiology, Chemistry, Biology, Medical, Plasmid Purification.

Also known as Laboratory Single Channel Pipette, Laboratory Large Capacity Pipette.

PIP14-01100E LARGE CAPACITY PIPETTE

Ergonomic design, exquisite appearance, comfortable and convenient operation, can be adapted to super-long pipette. Easy to use,

precise control

Adjust the pipetting speed with the button, 6 kinds of aspirate fluid 5 dispense speeds adjustable, unique gravity drainage mode,

especially useful for small volume pipetting

New pipetting pump, large power, can remove the large-capacity liquid rapidly. With a strong blow function to prevent residual

droplets, to ensure the accuracy of pipetting

Top large LCD display screen shows the current aspirate and dispense speed or gravity dispense; display battery power, when the

battery power is low, the beep sounds prompt charging

The entire electric pipette is light weight, maximum to prevent muscle strain.

Equipped with a desktop pipette holder, can be placed

on the desktop, achieve seat charging

New built-in lithium battery, using a special circuit design, to prevent the battery from overcharging. One time charge,

can intermittent work 8 hours, charging time 2-3 hours

Equipped with hydrophobic filter. Effectively prevent excessive liquid into the gun body, to prevent cross-contamination



SPECIFICATIONS

| Model | PIP14-01100E |
|-----------------------|---|
| Pipette type | 0.1 ~ 100 ml glass and plastic pipette, Pasteur pipette |
| Aspirate Speeds | 6 speed adjustable |
| Dispense Speeds | 6 speed adjustable with gravity dispense |
| Battery | Replaceable lithium battery |
| Battery Service Life | Intermittently at least 8 hours of normal use |
| Charging time | About 2 hours |
| Filtration membranes | 0.45 μ m hydrophobic membranes |
| Charging power supply | DC4.2 V 500 mAh |
| Dimensions (WxDxH) | W.30xD.161xH.147 mm |
| Net weight | 0.65 kgs |



Labstac LLC

82 Wendell Avenue, STE 100, Pittsfield, MA, 01201, USA
Email: contact@labstac.com | Website: labstac.com