

AUTOMATIC POLARIMETER POL11-30



AUTOMATIC POLARIMETER POL11-30

A polarimeter is an instrument used for determining the polarisation direction of the light or the rotation of an optically active substance.

Used in pharmaceutical, petroleum, food, chemicals, flavors, spices, sugar marking, universities, research institutes.

Also known as Polarimeter, Auto Polarimeter, Auto Digital Polarimeter.

POL11-30 AUTOMATIC POLARIMETER

The Peltier system automatically controls the sample temperature in the Automatic Polarimeter max range from 10 °C to 50 °C.

For calibration Additional Standard polarization tubes with software can be used by user.

Large color touch screen display and innovative software interface give extremely convenient device operation and data acquisition.

5.6 inch touch screen.

High brightness LED lights with service life exceeding 100000 hours. To void the light source exchanging.



SPECIFICATIONS

Model	POL11-30
Measuring Range	$\pm 89.99^\circ \text{Arc}$; $\pm 259^\circ \text{Z}$
Measuring Model	Optical Rotation; Specific Rotation; Concentration; Sugar Degree
Min. Reading	0.001° (optical rotation)
Accuracy	$\pm 0.01^\circ$ ($-45^\circ \leq \text{optical rotation} \leq +45^\circ$); $\pm 0.02^\circ$ (optical rotation $< -45^\circ$ or optical rotation $> +45^\circ$)
Repeatability (standard deviation)	0.002° (optical rotation)
Temperature Control	Peltier
Temperature Control Range	$10^\circ \text{C} \sim 50^\circ \text{C}$
Temperature Control Accuracy	0.3°C
Temperature resolution	0.1°C
Communication Port	USB×3, RS232, Wi-Fi
Data Storable	8GB
Tamper-proof data output	Yes
Display	8 inch
Sample Cell	Upto 200mm
Graphic	4 hours
Power	220V AC ($\pm 10\%$) 50Hz
Calibration (rotation value)	Optional
Optional Parts	Sample tubes, including corrosion-resistant tubes or micro tubes



Labstac LLC

82 Wendell Avenue, STE 100, Pittsfield, MA, 01201, USA
Email: contact@labstac.com | Website: labstac.com