

# HIGH TEMPERATURE HIGH SHEAR VISCOSITY METER PTL14-05



# HIGH TEMPERATURE HIGH SHEAR VISCOMETER

## PTL14-05

Viscosity of an oil is defined as its resistance to flow and Viscometer measures the flow. Monitoring viscosity is one of the most important components of any oil analysis program. Minute changes in viscosity at operating temperatures can be magnified to the extent that an oil is no longer able to provide adequate lubrication and efficiency in preventing friction between moving parts.

Used in Petroleum Industry, Oil and Gas Industry.

## PTL14-05 HIGH TEMPERATURE HIGH SHEAR VISCOMETER

Allow 24 hours continuous working for 365 days. Shear rate and test temperature can be set as per requirements. Automatically advise test pressure. Make Excel test report



### SPECIFICATIONS

Model	PTL14-05
Test units	5
Test samples	10 - 20 every hour
Calibration error of standard oil	Automatically calculated
Working Conditions	24 hours continuous working for 365 days
Shear rate and test temperature	Can be set as per requirements

# LABSTAC

**Labstac LLC**

82 Wendell Avenue, STE 100, Pittsfield, MA, 01201, USA  
Email: [contact@mail.labstac.com](mailto:contact@mail.labstac.com) | Website: [labstac.com](http://labstac.com)