

AUTOMATIC CAPILLARY VISCOMETER WASHER PTL18-80



AUTOMATIC CAPILLARY VISCOMETER WASHER

PTL18-80

Viscosity of an oil is defined as its resistance to flow and Viscometer measures the flow. Monitoring viscosity is one of the most important components of any oil analysis program. Minute changes in viscosity at operating temperatures can be magnified to the extent that an oil is no longer able to provide adequate lubrication and efficiency in preventing friction between moving parts.

Used in Petroleum Industry, Oil and Gas Industry.

PTL18-80 AUTOMATIC CAPILLARY VISCOMETER WASHER

It adopts micro-controller control technology, program control, automatic washing. It needs less solvent oil and it is convenient, efficient. It can be widely used in the enterprises producing and using petroleum products, colleges and universities, and scientific research institutes and so on, where capillary viscometer are used. High degree automation.



SPECIFICATIONS

Model	PTL18-80
Water bath temperature control range	Ambient to 80 °C
Ambient temperature	15 °C ~ 35 °C
Relative humidity	≤ 85 %
Maximum power consumption	700 W
Power supply	AC (220 ± 10%) V, 50 Hz
Dimension	320×300×500 mm (excluding the aspirator)
Net weight	24kg (excluding the aspirator)

LABSTAC

Labstac LLC

82 Wendell Avenue, STE 100, Pittsfield, MA, 01201, USA

Email: contact@labstac.com | Website: labstac.com