

# HYDROLYTIC STABILITY TESTER PTL2E-04



# HYDROLYTIC STABILITY TESTER PTL2E-04

Petroleum testing is the analysis during upstream, midstream, and downstream production processes of petroleum products. It is most commonly used to test petroleum product, its product components, byproducts of crude oil, fuel, natural gas, upstream oil and gas and other formats of petroleum.

Used in Petroleum Industry, PVC Pipe Industry.

## PTL2E-04 HYDROLYTIC STABILITY TESTER

Air cooling system starts heat radiation automatically when temperature of instrument surface is too high. New V type door opening mode, completely transparent high temperature resistant glass door.



## SPECIFICATIONS

Model	PTL2E-04
Samples size	4 groups sample expandable to 8 groups
Sample bottle	Automatic 360° turn
Air cooling system	Starts heat radiation automatically when temperature of instrument surface is too high
Enamel tank	High quality, corrosion resistant, easy to clean with fan circulation and lighting.
Door	New V type door opening mode, completely transparent high temperature resistant glass door.

# LABSTAC

**Labstac LLC**

82 Wendell Avenue, STE 100, Pittsfield, MA, 01201, USA

Email: [contact@labstac.com](mailto:contact@labstac.com) | Website: [labstac.com](http://labstac.com)