

# FOAMING CHARACTERISTICS TESTER PTL2F-02



# FOAMING CHARACTERISTICS TESTER PTL2F-02

Petroleum testing is the analysis during upstream, midstream, and downstream production processes of petroleum products. It is most commonly used to test petroleum product, its product components, byproducts of crude oil, fuel, natural gas, upstream oil and gas and other formats of petroleum.

Used in Petroleum Industry, PVC Pipe Industry.

## PTL2F-02 FOAMING CHARACTERISTICS TESTER

Separated structure, including main unit, gas source controlled. Sputtering turbine stirrer guarantees temperature uniformity. Touch screen operation, segment timing foam volume with buzzer prompt (optional).



## SPECIFICATIONS

Model	PTL2F-02
Units	Main unit and gas source controller
Flow meter	Electronic, controls flow at $94 \pm 5$ ml/min (optional)
Air filter	With molecular sieve
Bath	Refrigerated, 360° circulating, complete transparent.
Holding device	Special holding device, can prevent cylinder floating upward very well press block is unnecessary.
Stirrer	Sputtering turbine stirrer guarantees temperature uniformity
Safety device	Avoids over-heating or low liquid level
Operation	Touch screen
Optional	Segment timing foam volume with buzzer prompt.

# LABSTAC

**Labstac LLC**

82 Wendell Avenue, STE 100, Pittsfield, MA, 01201, USA  
Email: [contact@mail.labstac.com](mailto:contact@mail.labstac.com) | Website: [labstac.com](http://labstac.com)