

# THERMAL STABILITY TESTER PTL2G-08



# THERMAL STABILITY TESTER PTL2G-08

Petroleum testing is the analysis during upstream, midstream, and downstream production processes of petroleum products. It is most commonly used to test petroleum product, its product components, byproducts of crude oil, fuel, natural gas, upstream oil and gas and other formats of petroleum.

Used in Petroleum Industry, PVC Pipe Industry.

## PTL2G-08 THERMAL STABILITY TESTER

Heating aluminum black is placed in tank directly, with bracket. High quality enamel tank has fan circulation and lighting inside. New V type door opening mode, completely transparent high temperature resistant glass door.



## SPECIFICATIONS

Model	PTL2G-08
Samples size	8 groups sample simultaneously
Air cooling system	Starts heat radiation automatically when temperature of instrument surface is too high
Tank	High quality enamel tank, corrosion resistant and easy to clean
Fan	With fan circulation and lighting inside.
Door	New V type door opening mode, completely transparent high temperature resistant glass door.

# LABSTAC

**Labstac LLC**

82 Wendell Avenue, STE 100, Pittsfield, MA, 01201, USA  
Email: [contact@mail.labstac.com](mailto:contact@mail.labstac.com) | Website: [labstac.com](http://labstac.com)