

AUTOMATIC COC FLASH POINT TESTER PTL2W-48



AUTOMATIC COC FLASH POINT TESTER

PTL2W-48

Petroleum testing is the analysis during upstream, midstream, and downstream production processes of petroleum products. It is most commonly used to test petroleum product, its product components, byproducts of crude oil, fuel, natural gas, upstream oil and gas and other formats of petroleum.

Used in Petroleum Industry, PVC Pipe Industry.

PTL2W-48 AUTOMATIC COC FLASH POINT TESTER

The instrument adopts LCD screen to display. It is applicable to all petroleum products with flash points above 79°C and below 400°C except fuel oils. Differential coefficient detection. Automatically correct the system deviation.



SPECIFICATIONS

Model	PTL2W-48
Mode	Electric ignition
Ignition mode	
Gas flame diameter	3.2 mm~4.8 mm
Flash point determination	
Range	Ambient to 400°C
Repeatability	≤ 8°C (Flash Point)
Reproducibility	≤ 17 °C (Flash Point)
Ambient temperature	(10~40) °C
Power supply	AC (220±10%) V, 50Hz
Maximum power consumption	500 W
Dimension	460×430×290 mm
Net weight	22.5 kg

LABSTAC

Labstac LLC

82 Wendell Avenue, STE 100, Pittsfield, MA, 01201, USA
Email: contact@mail.labstac.com | Website: labstac.com