

# **AUTOMATIC DEMULSIBILITY CHARACTERISTICS TESTER PTL2Z12-04**



# AUTOMATIC DEMULSIBILITY CHARACTERISTICS TESTER PTL2Z12-04

Petroleum testing is the analysis during upstream, midstream, and downstream production processes of petroleum products. It is most commonly used to test petroleum product, its product components, byproducts of crude oil, fuel, natural gas, upstream oil and gas and other formats of petroleum.

Used in Petroleum Industry, PVC Pipe Industry.

## PTL2Z12-04 AUTOMATIC DEMULSIBILITY CHARACTERISTICS TESTER

The instrument is suitable to determine the water separability of petroleum oils and synthetic fluids. It adopts LCD to show the diagram. Intuitive and clear. Man-machine dialog. Menu type input. Easy to use.



### SPECIFICATIONS

Model	PTL2Z12-04
Testing hole	4 sample
Stirring rate	(1500±15)r/min
Stirring time	(0~99)min
Timing	(0~99)h
Temperature range	(Room temp.~110)°C
Temperature control accuracy	±0.02°C
Ambient temperature	5°C~40°C
Relative humidity	≤ 85%
Power supply	AC(220±10%)V, 50Hz
Maximum power consumption	1500W

# LABSTAC

**Labstac LLC**

82 Wendell Avenue, STE 100, Pittsfield, MA, 01201, USA

Email: [contact@labstac.com](mailto:contact@labstac.com) | Website: [labstac.com](http://labstac.com)