

DISTILLATION TESTER PTL2Z2-35



DISTILLATION TESTER PTL2Z2-35


Petroleum testing is the analysis during upstream, midstream, and downstream production processes of petroleum products. It is most commonly used to test petroleum product, its product components, byproducts of crude oil, fuel, natural gas, upstream oil and gas and other formats of petroleum.

Used in Petroleum Industry, PVC Pipe Industry.

Also known as Distillation Apparatus.

PTL2Z2-35 DISTILLATION TESTER

The instrument is suitable to determine the distillation characteristics of gasoline, aviation gasoline, jet fuels, solvent having special boiling point, naphtha, diesel oil, distillate fuels, and other petroleum products. It is not only suitable to the organizations of high frequency with various of samples but also accelerate the test speed for common users. It is an ideal distillation tester for petroleum products. The instrument adopts double units working mode.



Product Image Coming Soon

SPECIFICATIONS

Model	PTL2Z2-35
Distillation flask	125 ml
Receiving cylinder	100 ml, scale division 1 ml
Temperature controller	
Range	(Ambient + 10)°C ~ 60°C
Accuracy	±0.5°C
Display	LED
Thermometer	(-2~300)°C and (-2~400)°C, division value 1°C
Flask support board	Sic, bore diameter ϕ 32mm, ϕ 38mm, ϕ 50mm
Ambient temperature	15°C ~ 35°C
Relative humidity	≤ 85%
Power supply	AC(220±10%)V, 50Hz
Total power consumption	≤4000W
Dimension	760×520×500 mm
Net weight	40 kg

LABSTAC

Labstac LLC

82 Wendell Avenue, STE 100, Pittsfield, MA, 01201, USA

Email: contact@mail.labstac.com | Website: labstac.com