

DISTILLATION TESTER PTL2Z2-60



DISTILLATION TESTER PTL2Z2-60


Petroleum testing is the analysis during upstream, midstream, and downstream production processes of petroleum products. It is most commonly used to test petroleum product, its product components, byproducts of crude oil, fuel, natural gas, upstream oil and gas and other formats of petroleum.

Used in Petroleum Industry, PVC Pipe Industry.

Also known as Distillation Apparatus.

PTL2Z2-60 DISTILLATION TESTER

The instrument is suitable to determine the distillation characteristics of gasoline, aviation gasoline, jet fuels, and solvent having special boiling point, naphtha, diesel oil, distillate fuels and similar petroleum products. It adopts a special heating furnace to ensure the safety. The heating power can be adjusted continuously. The rising up and lowering down of distillation flask can be adjusted free by lifting device. Flexible and convenient to operate.



Product Image Coming Soon

SPECIFICATIONS

Model	PTL2Z2-60
Distillation flask	125 ml
Water bath temperature controlling	
Range	(ambient temp.+10) °C ~60°C
Accuracy	±0.5°C
Receiving cylinder	100ml, scale division 1ml
Ambient temperature	15°C~35°C
Relative humidity	≤ 85%
Power supply	AC(220±10%)V, 50Hz
Total power consumption	≤2000W
Dimension	460×400×550 mm
Net weight	18.5kg

LABSTAC

Labstac LLC

82 Wendell Avenue, STE 100, Pittsfield, MA, 01201, USA

Email: contact@labstac.com | Website: labstac.com