

DROPPING POINT TESTER (OIL BATH) PTL2Z21-06



DROPPING POINT TESTER (OIL BATH)

PTL2Z21-06

Petroleum testing is the analysis during upstream, midstream, and downstream production processes of petroleum products. It is most commonly used to test petroleum product, its product components, byproducts of crude oil, fuel, natural gas, upstream oil and gas and other formats of petroleum.

Used in Petroleum Industry, PVC Pipe Industry.

PTL2Z21-06 DROPPING POINT TESTER (OIL BATH)

The oil bath is composed of heat resistant beaker, heater and electric motor. The heating power can be adjusted continuously. The temperature in oil bath is uniform. Desktop structure. Easy to operate



Product Image Coming Soon

SPECIFICATIONS

Model	PTL2Z21-06
Oil Bath	600ml Beaker
Grease Cup	It is made of chrome plated brass, inner diameter: 9.92mm, oil dripping hole:2.8mm, cup height: 12mm
Test Tube	Heat resistant borosilicate glass tube with edge, inner diameter: 11.1 mm to 12.7 mm, and there are three grooves on the circumference 19 mm away from the bottom to support the grease cup
Stirring motor	60 R / min
Working environment: Temperature	(- 5 ~ 300) °C
Relative humidity	≤ 85%
Total power consumption	≤900W
Power supply	AC(220±10%)V, 50Hz
Dimension	350×180×410 mm
Net weight	8 kg

LABSTAC

Labstac LLC

82 Wendell Avenue, STE 100, Pittsfield, MA, 01201, USA

Email: contact@labstac.com | Website: labstac.com