

PETROLEUM PRODUCTS COLOR TESTER PTL2Z25-02



PETROLEUM PRODUCTS COLOR TESTER

PTL2Z25-02

Petroleum testing is the analysis during upstream, midstream, and downstream production processes of petroleum products. It is most commonly used to test petroleum product, its product components, byproducts of crude oil, fuel, natural gas, upstream oil and gas and other formats of petroleum.

Used in Petroleum Industry, PVC Pipe Industry.

PTL2Z25-02 PETROLEUM PRODUCTS COLOR TESTER

The instrument is composed of standard color dial, observation lens, light source and color comparing tube. The color dial is rotated by a hand wheel installed at right side of instrument to choose the correct color during color comparing test. The color comparing tube is placed into instrument trough a lid on the top of the instrument. The observation lens is composed of concave mirror and separated bar. You can see two semicircle colors through observation lens. The right semicircle is standard color. The light and focus of optical observation lens can be adjusted, so it is easy to be used.



SPECIFICATIONS

Model	PTL2Z25-02
Light_source	220 V, 100 W
Light source	
temperature	2750±50 K
Observation lens composition	concave mirror and separated bar
Standard color dial	26 pieces of Φ14 light holes
Color comparing tube	Φ32 mm, 120~130 mm high non-colorful flat bottom glass tube

LABSTAC

Labstac LLC

82 Wendell Avenue, STE 100, Pittsfield, MA, 01201, USA

Email: contact@labstac.com | Website: labstac.com