

2°C-10°C MEDICAL REFRIGERATOR REF11-520



2°C-10°C MEDICAL REFRIGERATOR REF11-520

Engineered to meet the demanding requirements of laboratory research. Major feature like forced air circulation system makes this product highly effective and reliable to provide quick freezing. Designed Environment friendly with no ozone-damaging chemicals and space saving with easier cleanability.

Used in Industry, Cosmetic, Pharmaceutical, Electronics, Laboratory, Medical, Research.

Also known as Laboratory Medical Refrigerator.

REF11-520 2°C-10°C MEDICAL REFRIGERATOR

Microprocessor controller, temperature ranging from +2°C to +8°C, can be set freely, controlling precision 1°C, display accuracy 0.1°C. Room temperature ranging from 0°C to 32°C

Combined with two exact sensors and auto defrost

Audible and visual alarm

Upright type, Exterior made from structural plate, interior made from stainless steel,

Four units Caster are mounted under the bottom

Two-layer glass door, and inert gas inside. and lockable

Interior fluorescent lighting

Adjustable 4-5 units shelves made of quality steel wire

Forced air circulation system

Highly effective condenser and expansile evaporator to provide quick freezing

Optional: temperature printer or chart recorder



SPECIFICATIONS

Model	REF11-520
Capacity	520 L
Temperature Range	2~8°C
Refrigerant	R134a, CFC free
Refrigeration System	International famous compressor and Germany EBM fan motor
Controller	Microprocessor Control with LCD Display
Alarms	High & low temperature alarm, Door open alarm, Sensor failure alarm
External Size	710x785x1975 mm
Package Size	870x990x2150 mm
Optional Accessories	Remote alarm system
Weight	120/140 Kgs
Power	300W
Power Supply	220V,50/ 60HZ, 110V,50/60HZ

LABSTAC

Labstac LLC

82 Wendell Avenue, STE 100, Pittsfield, MA, 01201, USA

Email: contact@labstac.com | Website: labstac.com