

2°C-10°C MEDICAL REFRIGERATOR REF13-100T



2°C-10°C MEDICAL REFRIGERATOR REF13-100T

Engineered to meet the demanding requirements of laboratory research. Major feature like forced air circulation system makes this product highly effective and reliable to provide quick freezing. Designed Environment friendly with no ozone-damaging chemicals and space saving with easier cleanability.

Used in Industry, Cosmetic, Pharmaceutical, Electronics, Laboratory, Medical, Research. Also known as Laboratory Medical Refrigerator.

REF13-100T 2°C-10°C MEDICAL REFRIGERATOR

Undercounter Mini type



SPECIFICATIONS

Model	REF13-100T
Capacity	60 L
Temperature Range	2~8°C
Ambient Temperature	10~32°C
Refrigerant	R600a
Defrost Method	Auto Defrost
Controller	Microprocessor Control with digital Display
Control Sensor	NTC
Cooling Type	Forced air cooling
Shelf/drawer	Shelves/2
Alarms	High/low temperature, Power failure, Thermostat failure, Door ajar, Power failure backup system(alarm) 8h
Insulation	PURF
Material Inside	Color sprayed steel
Material Outside	Color sprayed steel
Noise Level	50 dB
Internal Size	410x315x560 mm
External Size	495x450x710 mm
Package Size	558x510x760 mm
CBM	0.22
20GP/40GP/40HQ	132/276/276
NT./GT. (kg)	33/37kg
Power consumption (kW.h/24h)	0.84

om

2

Power	72W
Current (A)	0.59A
Voltage/frequency (V/Hz)	220/50Hz
Standard Accessories	Foot, Type Low-E outer Glassdoor, Door Lock, Test hole 25mm diameter, Remote alarm port, LED Lamp
Optional Accessory	USB port, Temperature recorder Datalogger



Labstac LLC

82 Wendell Avenue, STE 100, Pittsfield, MA, 01201, USA Email: contact@labstac.com | Website: labstac.com