

4°C BLOOD BANK REFRIGERATOR REF23-368



4°C BLOOD BANK REFRIGERATOR REF23-368

Designed as an essential piece of equipment in the immunohematology department and provides safe and convenient storage of whole blood, blood components, reagents and ensures freshness and integrity of blood and blood components. Microprocessor integrated system provides excellent temperature accuracy and reliable performance. Used in Immunohematology Department, Blood Bank, Laboratory, Research, Medical, Pharmaceutical. Also known as Laboratory Blood Bank Refrigerator.

REF23-368 4°C BLOOD BANK REFRIGERATOR

450ml blood bag x 200



SPECIFICATIONS

| | |
|----------------------|--|
| Model | REF23-368 |
| Capacity | 368 L |
| Temperature Range | +4°C±1 |
| Ambient Temperature | 10~32°C |
| Bloodbags(450ml) | 200 |
| Refrigerant | R134a |
| Defrost Method | Auto Defrost |
| Controller | Microprocessor Control with digital Display |
| Control Sensor | NTC |
| Cooling Type | Forced air cooling |
| Compressor brand/QTY | EMBRACO/1 |
| Shelf/drawer | Shelves/4 |
| Alarms | High/low temperature, Power off, Temperature controller malfunction, Backup battery malfunction, 8h Power failure backup system(alarm) |
| Insulation | PURF |
| Material Inside | Stainless steel |
| Material Outside | Color sprayed steel |
| Internal Size | 685×429×1380 mm |
| External Size | 785×565×1920 mm |
| Package Size | 890×650×2100 mm |
| CBM | 1.21 |
| 20GP/40GP/40HQ | 21/44/44 |
| NT./GT. (kg) | 128/135 |

| | |
|------------------------------|---|
| Power consumption (kW.h/24h) | 4.28 |
| Power | 325W |
| Current (A) | 2.2A |
| Voltage/frequency (V/Hz) | 220/50Hz |
| Standard Accessories | Caster, 1 Heating & Foam glass door type outdoor, 4 Inner door, Test hole 25mm, Thermal Printer, LED Light, |
| Optional Accessory | Temperature recorder Datalogger |

LABSTAC

Labstac LLC

82 Wendell Avenue, STE 100, Pittsfield, MA, 01201, USA
Email: contact@mail.labstac.com | Website: labstac.com