

# INCUBATOR SHAKER SHA022-30B



# INCUBATOR SHAKER SHA022-30B

## SHA022-30B INCUBATOR SHAKER

Adopt 4.3 inches touch screen , intelligent touch screen control, parameters real time display, operation easily

Temp., rotation speed and time etc parameters fast setting

Combine incubator, shaker functions together with small space, huge capacity

Colorful touch screen controller, menu operation interface, multi datas display at one screen, easily to observe and operate

Fluorine free design

PID microcomputer control temp. and shake frequency with timer

Compressor and cycle fan etc key components are reliable suppliers, environmental non-free refrigerants.

Brushless DC motor, large start torque, wide speed adjustment, free maintenance

The ultraviolet lamp can sterilize the chamber regularly

CO2 concentration monitor and control

Lighting control(Stimulate the nature growth environment)

Humidity monitor and control



## SPECIFICATIONS

Model	SHA022-30B
Speed Range	40-300 rpm
Power Supply	AC 220 V 50 HZ
Amplitude	20 mm
Temp. Control Range	4 - 65°C
Temperature Resolution	0.1°C
Uniformity(at 37°C )	±0.5°C
Timing Range	0 - 99h59 min
Platform Dimension	500x420 mm
Overall Dimension	725Wx720Dx1055H mm
Power	1300 W

# LABSTAC

**Labstac LLC**

82 Wendell Avenue, STE 100, Pittsfield, MA, 01201, USA

Email: [contact@labstac.com](mailto:contact@labstac.com) | Website: [labstac.com](http://labstac.com)