

# INCUBATOR SHAKER SHA023-21B



# INCUBATOR SHAKER SHA023-21B

## SHA023-21B INCUBATOR SHAKER

Adopt 4.3 inches touch screen , intelligent touch screen control, parameters real time display, operation easily

Temp, rotation speed and time etc parameters fast setting

Combine incubator, shaker functions together with small space, huge capacity.

Colorful touch screen controller, menu operation interface, multi data display at one screen, easily to observe and operate

Silent running

Fluorine-free design, environmental friendly

Big transparent big view windows, platform and chamber are made of stainless steel, anti-corrosion and easy to clean

Brushless DC motor, large start torque, wide speed adjustment, free maintenance

Sterilization system: The ultraviolet lamp can sterilize the chamber regularly

Protection on instruments: Comply international standard secondary temp. limiter alarm system, alert the operator with sound and light alarms, ensure operator is safe without any accident

Protection on key components: Key components have over current, over temp., over load etc safety protection, it can prevent instruments accidents without precautions

CO2 concentration monitor and control

Lighting control

Humidity monitor and control



## SPECIFICATIONS

Model	SHA023-21B
Speed Range	40-300 rpm
Power Supply	AC 220 V 50 HZ
Amplitude	26 mm
Temp. Control Range	4 - 80°C
Temperature Resolution	0.1°C
Timing Range	1 - 99h59 min
Platform Dimension	750x460 mm
Overall Dimension	1060Wx680Dx910H mm
Power	1300 W
Standard configuration	250mlx28

# LABSTAC

**Labstac LLC**

82 Wendell Avenue, STE 100, Pittsfield, MA, 01201, USA

Email: [contact@labstac.com](mailto:contact@labstac.com) | Website: [labstac.com](http://labstac.com)