LABSTAC

COOLED SHAKING INCUBATOR SHA14-300

labstac.com

COOLED SHAKING INCUBATOR SHA14-300

Highly efficient insulation guarantees homogeneous temperature dispersion as well as reproducible cultivation results and combines uniform, reliable performance with low energy consumption. Suitable for cell culturing, solubility studies, sample preparation, water analysis, BOD measurement, plating and breeding experiments in research institutions, universities and colleges.

Used in Cell Culturing, Cell Aeration, Solubility Studies, Sample Preparation, Water Analysis, BOD Measurement, Plating, Breeding Experiments, Research Institutions, Universities, Colleges.

Also known as Cooled Shaking Incubator, Shaker Incubator, Laboratory Cooled Shaking Incubator.

SHA14-300 COOLED SHAKING INCUBATOR

Microprocessor controller
Stainless steel interior and Electrostatic sprayed exterior
LCD display

SPECIFICATIONS

Model	SHA14-300
Speed Range	20-300 rpm
Standard Capacity	2000 mlx8
Temperature	4°C~60°C
Temperature Accuracy	±0.1°C
Temperature Uniformity	±1°C
Shaking Speed Accuracy	±1 rpm
Timing Range	Optional
Motion	Orbital
Amplitude	26 mm
Tray	1
Platform Dimension	920x500 mm
Overall Dimension	1100x765x890 mm
Display	LCD
Weight	183 kg
Power	1800 W
Power Supply	220 V, 60 Hz

Labstac LLC
82 Wendell Avenue, STE 100, Pittsfield, MA, 01201, USA
Email: contact@labstac.com | Website: labstac.com