

**LABSTAC**

# INCUBATOR SHAKER SHA2A-0300



# INCUBATOR SHAKER SHA2A-0300

In Incubator Shaker, the constant agitation with uniform amplitude provides the optimum oxygen transfer to the cultures, leading to better and consistent yield. A variety of platforms and different laboratory accessories permits configuration to fulfill your demands.

Used in Cell Cultures, Cell Aeration, Microbiology, Increasing Solubility Rates, Metabolism Studies, Bacterial Cultures, Bacteriology.

Also known as Laboratory Incubator Shaker, Incubator Shaker.

## SHA2A-0300 INCUBATOR SHAKER

The electronic control of closed cycle adjustable heating system

Sainless steel interior and Electrostatic sprayed exterior

Call to restore function, without power supply

With strong influence of intermittent rapid heating system of.200 type and 100B type with air pressure regulating valve

Flexible and convenient, wide variety of detachable accessories



## SPECIFICATIONS

Model	SHA2A-0300
Speed Range	20-300 rpm
Standard Capacity	500 mlx4, 250 mlx4, 100 mlx5, 50 mlx5
Temperature	4°C~60°C
Temperature Accuracy	±0.1°C
Temperature Uniformity	±1°C
Shaking Speed Accuracy	±1 rpm
Timing Range	Optional
Motion	Orbital
Amplitude	26 mm
Tray	1
Platform Dimension	450x400 mm
Inner Dimension	508x458x360 mm
Overall Dimension	800x700x530 mm
Display	LCD
Weight	100 kg
Power	580 W
Power Supply	220 V±10%

***LABSTAC***

**Labstac LLC**

82 Wendell Avenue, STE 100, Pittsfield, MA, 01201, USA  
Email: [contact@labstac.com](mailto:contact@labstac.com) | Website: [labstac.com](http://labstac.com)