

MICROPLATE SHAKER SHA33-1600



MICROPLATE SHAKER SHA33-1600

Microplate Shaker is ideal for applications requiring precise speed control or pulse vortexing. Features true pulsing action for a more random motion and thorough mixing. It comes with interchangeable clamps for different micro plates which makes it universally fit.

Used in Mixing, Incubation, Cultivation, Microbiology, Molecular biology, Biotechnology, Immunoassays, HTS applications, Colouration tests, Binding.

Also known as Laboratory Microplate Shaker, Microplate Shaker.

SHA33-1600 MICROPLATE SHAKER

Orbital of 3mm for efficient mixing in small sample vessels

Heated lid prevents condensation

Accepts a variety of microplates

Easy to operate with one touch knob



SPECIFICATIONS

Model	SHA33-1600
Speed Range	200-1600 rpm
Capacity	2 microplates
Temperature	Ambient 8°C~70°C
Temperature Stability @37°C	±0.3°C
Display Accuracy	0.1°C
Speed Increment	1 rpm
Time of Heating	<25 min (from 20°C to 70°C)
Timing Range	1 min~99 h 59 min or continuous
Motion	Orbital
Overall Dimension	280x270x140 mm
Power Supply	110 V/220 V, 60/50 Hz, max.150 VA

LABSTAC

Labstac LLC

82 Wendell Avenue, STE 100, Pittsfield, MA, 01201, USA

Email: contact@labstac.com | Website: labstac.com