

3D SHAKER SHA51-080



3D SHAKER SHA51-080

Allows for easy and accurate rack placement, data retrieval on power failure and slow start up function prevents liquid spillage. Applications like stability and dissolution studies, liquid extractions, protein precipitation studies, small peptide synthesis and dilutions makes it an ideal choice.

Also known as Laboratory Orbital Shaker.

SHA51-080 3D SHAKER

Real-time speed display and timing display, convenient and intuitive. Can be set to run continuously from time to time.

With a timing alarm system, when the program is finished, there will be a buzzer prompt.

Speed is adjustable, the speed range is 5 ~ 80rpm.

Special movement structure, strong bearing capacity and low running noise



SPECIFICATIONS

Model	SHA51-080
Speed Range	5~80 rpm
Timing Range	0~99 h 59 min
Angle of inclination	16°
Operation mode	Timing/continuous operation
Maximum load	2.5 kg
Power	35 W
Fuse	250 V,1 A,φ5x20
Voltage	AC110~230V,50/60 Hz
Overall Dimension	W.368xD.228xH.206 mm
Net weight	5.2 kg

OPTIONAL ACCESSORIES

Accessory Code	Name	Description
1901312005	Platform A	500 ml flask x 4
1901312006	Platform B	250 ml flask x 5
1901312007	Platform C	100 ml flask x 9
1901312008	Platform D	culture plate x 2
1901312009	Non-slip Pad	
1901312010	Convex Pad	

LABSTAC

Labstac LLC

82 Wendell Avenue, STE 100, Pittsfield, MA, 01201, USA
Email: contact@labstac.com | Website: labstac.com