

ORBITAL SHAKER SHA52-250



ORBITAL SHAKER SHA52-250

Allows for easy and accurate rack placement, data retrieval on power failure and slow start up function prevents liquid spillage. Applications like stability and dissolution studies, liquid extractions, protein precipitation studies, small peptide synthesis and dilutions makes it an ideal choice.

Used in Stability, Dissolution Studies, Liquid Extractions, Protein Precipitation, Small Peptide Synthesis, Dilutions. Also known as Laboratory Orbital Shaker.

SHA52-250 ORBITAL SHAKER

Microprocessor control with simultaneous display of time and speed
Compact space-saving design fits easily in incubator and refrigerator
Brushless DC motor ensures maintenance-free, reliable and quiet operation
Adjustable speed control provides gentle to vigorous agitation
Multi-functional shaking system
Audio alarm signals program completion

Accommodate a variety of platforms, non-slip rubber mat, conical flasks and other sample containers



SPECIFICATIONS

Model	SHA52-250
Speed Range	50-250 rpm
Temperature	Ambient +5-40°C
Shaking Orbit	20 mm
Timing Range	1 min~99 h 59 min
Motion	Orbital
Maximum Load Capacity	2.5 kg
Operation	Continuous/Timed
Overall Dimension	280x270x110 mm
Display	LED
Weight	7.2 kg
Power	50 W
Power Supply	AC90~240V, 50/60Hz, 2A



Labstac LLC

82 Wendell Avenue, STE 100, Pittsfield, MA, 01201, USA Email: contact@m.labstac.com | Website: labstac.com